




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> :  A61M 5/315, 5/50	AI	(11) International Publication Number: <b>WO 94/04208</b>  (43) International Publication Date: 3 March 1994 (03.03.94)
(21) International Application Number: PCT/SE93/00698 (22) International Filing Date: 23 August 1993 (23.08.93) (30) Priority data: 9202423-1                      25 August 1992 (25.08.92)      SE (71)(72) Applicant and Inventor: HELLDIN, Nils, Göran [SE/ SE]; Västergatan 46, S-533 22 Götene (SE). (74) Agent: LINDBLOM, Erik, J.; Flotthamn, S-150 23 Enhör- na (SE). (81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>	

(54) Title: A SYRINGE



## (57) Abstract

The invention relates to a syringe (1) which comprises a rod (5) mounted for reciprocating movement in relation to a container (2), wherein one end of the rod has the form of a needle (3) or is able to coact with a needle. The syringe further comprises a piston (4) and coupling means (6) which connect and disconnect the piston to and from the rod. The coupling means assume a connecting state when the piston is drawn by the rod from a position proximate to the needle to a position in which it is distanced therefrom, and are brought to a disconnecting or disconnected state when the piston is pressed by the rod towards the needle. The coupling means comprise support and/or slide surfaces (5k', 5k) arranged on that part of the rod which is proximal to the needle, and opposing support and/or slide surfaces (4k', 4k) on the piston. The first support and/or slide surfaces (4k') provided on the piston and located nearest the needle (3) are inclined (c) to an extent such that as the rod (5) moves towards the needle (3), the piston (4) is rotated about a container centre line, among others.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	CN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

## A Syringe

TECHNICAL FIELD

5

The present invention relates generally to a syringe and more particularly, although not exclusively, to a syringe which is intended for one time use only, i.e. a so-called disposable syringe, and which is of the kind that includes a rod which is fitted in a container for reciprocating movement in relation thereto and one end of which has the form of or coacts with a needle, a piston which is able to coact with the rod, and coupling means which function to connect and disconnect the piston to and from the rod.

15

The present invention is primarily intended to provide a syringe of this kind which is constructed so as to enable the container to be filled with liquid through the needle and the liquid then dispensed through said needle and so that after this the container can no longer be filled with and emptied of liquid.

20

The present invention pertains in particular to a syringe of the kind in which the coupling means which function to connect and disconnect the piston to and from the rod adopt an active coupling state over a movement path in which the piston is drawn by the rod from a position close to the needle to a position in which it is distanced from said needle, and is brought to a disconnected state when the piston is pressed by the rod through an adapted short movement path in a direction towards the needle, said coupling means comprising support and/or slide surfaces which are provided on that part of the rod which lies proximal to the needle and which coact with opposing support and/or slide surfaces on the piston in the coupled state of the rod and the piston.

30

35

BACKGROUND ART

5 Disposable syringes of the aforescribed kind, by which is meant syringes that can only be used once, can be divided into a number of function-dependent categories with regard to their function-dependent characteristics.

10 A first syringe category is exemplified by the syringe illustrated and described in the International Patent Publication PCT/SE88/00634, International Publication No. WO 89/04677. In the case of this syringe, the rod can be twisted in relation to the container and the  
15 piston so as to move the coupling means on the one hand to a connecting state and on the other hand to a disconnecting state, as the rod is twisted. Thus, with this type of syringe, it is necessary that the piston is unable to twist or rotate, or at least not essentially, at the same time as the rod is twisted in  
20 relation to the container.

It is thus of great importance with this category of syringe that means are provided to ensure that the  
25 piston will not twist together with the rod.

In a second syringe category, the rod, or rod unit, carries a piston or piston unit and moves backwards and forwards in the container without twisting, and  
30 the outer surface of the piston unit and the inner surface of the container include means which mutually coact to lock the piston in a lowermost position. Examples of these prior art syringe assemblies are described and illustrated in prior publications US-A  
35 4,391,272; US-A 4,775,364; PCT/GB87/00728 with respective International Publication Nos. WO 88/02640; GB-A 2,197,792 and FR-A 2,613,628.

A third category of disposable syringes includes a rod unit which is moved forwards and backwards in the container without twisting, and a piston unit which is fastened to the rod unit by means of a separate connecting part.

This connecting part is pivotally mounted on the rod part for rotation about a centre line on the rod, the piston and the container, and can be guided into different rotational positions by grooves disposed on the piston unit.

An example of this type of syringe is described and illustrated in publication NO-A 163,263.

#### DISCLOSURE OF THE PRESENT INVENTION

#### TECHNICAL PROBLEMS

When studying the earlier known art as described above, while considering the comprehensive efforts that have been made to construct a disposable syringe which is well adapted for mass production at a cost which is comparable with the cost of manufacturing standard reusable syringes, it will be seen that a qualified technical problem is one of realizing the possibility of moving the coupling means for connecting and disconnecting the piston to and from the rod to a desired connecting and desired disconnecting state or position, solely by providing conditions which will enable the piston to be rotated within the container.

Another technical problem is one of realizing the significance of providing conditions such that rectilinear movement of the rod in the container towards the needle, without twisting the rod, will cause desired rotation of the piston so that the piston unit will cease to coast with the rod unit upon restricted

rotational movement, such as rotation through less than one-half revolution.

5 Another technical problem is one of realizing the significance of adapting the supporting and/or sliding surfaces on the piston unit and/or the rod unit and by inclining said surfaces at an appropriate angle.

10 A further technical problem is one of realizing the significance of adapting the configuration of the opposing support and/or slide surfaces so as to adapt said surfaces to a desired degree of friction, and/or to a form in which they can be conveniently produced in a mould die.

15 Still another technical problem is one of realizing the advantages that are gained with regard to the operation of a syringe which is so constructed that when the piston is moved towards the needle so as to  
20 inject liquid contained in the container, the piston will generate a well-defined frictional force against the inner wet surface of the container, and therewith to realize the significance of choosing an appropriate angular value while considering the occurrent readily  
25 definable frictional conditions.

It will also be seen that a technical problem resides in realizing the significance of allowing the first support and/or slide surfaces provided on the piston  
30 proximal to the needle to slope at such an angle that as the rod is moved towards the needle, the piston will be twisted about a centre line on the container, among other centre lines, so as to bring said coupling means from a connected to a disconnected state in  
35 response to movement of the rod along a short movement path.

It will also be seen that a technical problem resides in realizing the significance of inclining said sur-

faces such that as the piston is rotated by the mutually coating surfaces over a chosen initial movement path, which at least equals less than half the maximum movement path of the rod in the container, the first support and/or slide surfaces on the piston will be distanced from corresponding first support and/or slide surfaces on the rod to a position in which the coating surfaces of said coupling means are disconnected.

10

It will also be seen that a technical problem resides in realizing the significance of displacing the piston and the rod to a mutually disconnected position over a small distance of less than one-quarter of the maximum movement path of the rod while still providing the desired function.

15

Another technical problem is one of realizing the significance of configuring the first support and/or slide surfaces on the rod so that said surfaces will coact selectively with corresponding first support and/or slide surfaces on the piston, wherein said contact surfaces can be either flat surfaces or linear surfaces, or alternatively punctiform surfaces, where at least the two latter surfaces shall slide against a continuous, preferably curved slide surface.

20

25

Another technical problem is one of realizing the significance of inclining the first support and/or slide surfaces on the piston and/or on the rod at a well-adapted angle to a centre line on the piston or the rod, among others.

30

A further technical problem is one of realizing the significance of inclining the second support and/or slide surfaces that are provided on the piston distal from the needle at an angle such that as the rod is moved away from the needle, the piston will be subjected to a force which acts on the second support

35

and/or slide surfaces on the rod such as to rotate the piston around a container centre line, said second support and/or slide surfaces holding the corresponding second support and/or slide surfaces in a mutually coacting or mutually engaging position.

Another technical problem is one of realizing the significance of adapting the configuration of the second support and/or slide surface on the rod to the second support and/or slide surface on the piston.

When considering the aforesaid circumstances, it will also be seen that a technical problem resides in the ability to choose angular limit values which will not only ensure a desired and positive aspiration function but also a positive function with respect to the remainder of the disposable syringe.

#### SOLUTION

With the intention of solving one or more of the aforesaid technical problems, the present invention departs from a syringe of the kind which includes a rod that can be moved reciprocatingly in relation to a container and one end of which is in the form of a needle or is intended to coact with a needle, and which further includes a piston which coacts with the rod, and coupling means for connecting and disconnecting the rod to and from the piston.

The coupling means which function to connect and disconnect the piston to and from the rod are mutually engaged when the piston is drawn by the rod from a needle-proximate position to a needle-distanced position, and is brought to a disconnecting and disconnected state when the piston is pressed initially by the rod through an adapted short movement path in a direction towards the needle, said coupling means comprising support and/or slide surfaces on that part



of the rod which is proximal to the needle and corresponding opposing support and/or slide surfaces on the piston, said surfaces coacting mutually in the coupled state of said coupling means.

5

In accordance with the invention, the first support and/or slide surfaces of the piston located nearest the needle are inclined to an extent such that as the rod is moved initially towards the needle, the piston is rotated about a container centre line, among others.

10

According to preferred embodiments that lie within the scope of the invention, the extent to which the piston is rotated by the inclined surfaces is adapted so that during said rod movement and after movement along a short movement path, which is less than half the maximum path of movement of the rod in the container, the first support and/or slide surfaces on the piston will leave the corresponding first support and/or slide surfaces on the rod so as to bring said coupling means to a disengaged state.

15

20

The angle at which said surfaces are inclined is preferably so adapted that the distance through which the rod moves in order to achieve aspiration can be chosen to be smaller than one-quarter of the maximum distance moved by the rod in the container.

25

According to one embodiment, the first support and/or slide surfaces on the rod may be configured for parallel, linear or punctiform cooperation with corresponding first support and/or slide surfaces on the piston.

30

It is especially preferred that the first support and/or slide surfaces on the piston and/or on the rod define an angle of between 85° and 20° with a centre line on the piston or the rod, among others.

35

One advantage afforded by the present invention is that the rod, in a known manner, can now be made straight and adapted for movement up and down in the container without twisting, with the inclusion of an associated simplified rod attachment and rod guide in the upper container part.

Furthermore, the second support and/or slide surfaces on that part of the piston which is distal from the needle are inclined to such an extent that as the rod is moved away from the needle, the piston will be subjected to a force which causes the piston to be rotated around a container centre line, among others, by the second support and/or slide surfaces on the rod, these latter surfaces holding the piston and its corresponding second support and/or slide surfaces in a coacting or co-engaging position.

According to one embodiment, the second support and/or slide surfaces on the rod are configured for parallel, linear or punctiform coaction with corresponding second support and/or slide surfaces on the piston.

#### ADVANTAGES

Those advantages primarily associated with an inventive disposable syringe are that the aforesaid coupling means remains in a coupled state when the piston is drawn by the rod from a position proximate to the needle to a position distanced therefrom, and are brought to a disconnecting or disconnected state when the piston is then pressed initially by the rod towards the needle, in that during axial movement in the container along a short displacement path, the first support and/or slide surfaces coacting on the piston and the rod will cause the piston to rotate so as to cause said coupling means to take a disengaging position, this being achieved solely by adapting the slope of the first support and/or slide surfaces in relation

to a piston centre line or a container centre line, among others.

5

-----

The primary characteristic features of an inventive disposable syringe are set forth in the characterizing clause of the following claim 1.

10

-----

BRIEF DESCRIPTION OF THE DRAWINGS

An exemplifying embodiment at present preferred and having properties significant to the present invention will now be described in more detail with reference to the accompanying drawings, in which

Figure 1 is a perspective view of the lower part of a rod and associated support and/or slide surfaces, and a piston with associated support and/or slide surfaces, and shows said surfaces in a mutually distanced and mutually disengaged position;

25

Figure 2 is a side view showing flat support and/or slide surfaces on the rod in engagement with flat support and/or slide surfaces on the piston, with the illustrated angular values being related to a centre line on the piston and the rod, among others;

30

Figures 3-5 are side views of alternative configurations of the support and/or slide surfaces on the rod;

35

Figure 6 illustrates a linear coaction surface between the support and/or slide surfaces of the piston and the rod; and

Figure 7 illustrates a punctiform coaction surface between the support and/or slide surfaces of the piston and the rod.

5 BEST MODES OF CARRYING OUT THE INVENTION

- Because the inventive syringe can be considered to constitute a direct development of the disposable syringe illustrated and described in International Patent Publication PCT/SE92/00258, reference is made to this publication for a closer description of the different components of the syringe and the manner in which they coact with one another.
- 10 To simplify matters, the same reference signs as those used in the aforesaid international patent publication have been used in the present drawing to identify similar components.
- 15 Thus, it can be seen that the present invention is based on a syringe 1 which comprises a rod 5 that can be moved reciprocatingly in relation to a container 2 (which is not shown in the Figure). One end of the rod 5, the lower end, has the form of a needle 3 (not shown) or is able to coact with said needle, a piston 25 4 which coacts with the rod, and coupling means 6 which function to connect and disconnect the piston to and from the rod.
- 20 As shown in Figures 2-7, the opposing surfaces of the coupling means 6 are mutually engaged as the piston is drawn by the rod from a position proximate to the needle 3 to a position in which the piston is distanced from the needle, and are disengaged when the piston 4 is pressed by the rod towards the needle 3. In the case of the first mentioned movement, the part 5a' is located further to the right than is shown in the Figures.
- 30
- 35

Figure 1 illustrates an operational state of the syringe in which the piston is located in its lowermost position upon completion of injecting the contents of the syringe, with the rod withdrawn slightly upwards without coacting with the piston.

The coupling means 6 is comprised of support and/or slide surfaces provided on that part 5a' of the rod which is proximal to the needle, and coacting, opposing and corresponding support and/or slide surfaces on the piston.

Figure 2 illustrates clearly the significant characteristics of the present invention, wherein the first support and/or slide surfaces 4k' provided on the piston 4 and located proximal to the needle 3 slope to such an extent that as the rod 5 is moved towards the needle 3, the piston 4 is rotated about a centre line 5' of the container, the rod, or the piston.

Naturally, rotational movement of the piston 4 in response to axial movement of the rod 5 will depend to a very large extent on the angle at which the support and/or slide surface 4k' are inclined. According to the present invention, the slope of said surfaces is adapted so that the first support and/or slide surfaces on the piston will move away from the corresponding first support and/or slide surfaces on the rod over a chosen, short movement path, which is shorter than half the maximum movement path of the rod in the container 3, so as to mutually disengage the coupling means. This is shown in broken lines in Figure 2.

The aforesaid movement path is conveniently chosen to correspond to a distance which is shorter than one-quarter of the maximum movement path of the rod, for instance a movement path which is shorter than 10 mm, normally somewhat shorter than 5-7 mm, to provide an aspiring function.

The first support and/or slide surfaces 5k' on the rod are configured so as to be parallel with the corresponding first and/or slide surfaces 4k' on the piston, as clearly shown in Figure 2.

5

There is nothing to prevent the slide surfaces 4k and/or 4k' from being curved, however, although the curve will preferably be continuous.

10

It is particularly recommended that the first support and/or slide surfaces on the piston and/or on the rod define an angle "c" of between 85° and 20° with a piston centre line or rod centre line 5'.

15

This angular value lies within those limits within which a practical function can be obtained, and a longer aspiration path is obtained at the lower values.

20

The surfaces may also be sloped at an angle which is adapted to the requisite sliding function.

A suitable angular value is between 80° and 45°, preferably between 75° and 65°.

25

Figure 1 shows an angular value of about 80°, whereas Figures 2-5 show an angular value of about 70°.

30

The rod 5 is straight and is adapted for rectilinear, reciprocating movement in the container 3 without twisting.

35

The second support and/or slide surfaces 4k located on the piston distal from the needle 3 slope to an extent such that in coaction with the second support and/or slide surfaces 5k on the rod, the piston will be subjected to a force which causes the piston to rotate about a container centre line, among other centre lines, as the rod 5 is moved away from the needle,

wherein the second support and/or slide surfaces 5k on the rod hold the corresponding second support and/or slide surfaces 4k in a mutually coacting or mutually engaging position.

5

In the case of the Figure 2 embodiment, the second support and/or slide surfaces 5k on the rod are parallel with the corresponding second support and/or slide surfaces 4k on the piston.

10

The angle "c" and the length of the groove can thus be chosen in accordance with the desired maximum aspiration length of the rod, among other things, and the maximum movement path desired between fully coacting or fully engaged position of the coupling means 6 and a guaranteed disengagement position.

15

The angle "c" shall thus be chosen so that as the rod 5 is moved away from the needle 3, the piston will be rotated into a fully coacting position, as illustrated by the position 4k".

20

In the exemplifying embodiment, the angular values "c" and "c'" are identical, although there is nothing to prevent these angles being different to one another.

25

It should be noted in this regard that as the piston 4 is moved towards the needle 3, the peripheral surface of the piston will slide along wet internal container surfaces, and that well-defined frictional conditions prevail during this movement of the piston, these conditions being observed primarily when choosing the value of the angle "c".

30

When moving the piston 4 away from the needle 3, the piston will slide along dry surfaces and the frictional conditions are more difficult to define. This circumstance should be taken into account when choosing the value of the angle "c'".

35

Figure 3 illustrates an embodiment in which the support and/or slide surface 5k' on the rod provides a linear or punctiform abutment surface with the flat or angled first support and/or slide surface 4k' on the piston.

The second support and/or slide surface 5k on the rod is flat and can coact with a flat or linear abutment surface against the second support and/or slide surface 4k on the piston.

Figure 4 illustrates an embodiment in which the support and/or slide surfaces on the rod 5 provide linear or punctiform abutment surfaces 5k' and 5k, corresponding to the configuration of the support and/or slide surfaces on the piston 4.

The embodiment illustrated in Figure 5 includes a flat first support and/or slide surface 5k' and a linear second support and/or slide surface 5k.

In the case of the Figure 6 embodiment, the first and second support and/or slide surfaces 4k' and 4k on the piston 4 are flat and parallel, whereas in the Figure 7 embodiment the surfaces 4k' and 4k are flat and inwardly converging. (There is nothing to prevent the surfaces from converging outwards).

As will be understood, it is conceivable within the scope of the invention to combine each detail in Figures 2-5 with each detail in Figures 6 and 7.

Depending on the chosen angle "c", it can be assumed that in the case of small angular values, the piston is able to rotate without moving longitudinally or while moving only slightly in a longitudinal direction, whereas in the case of large angular values, the piston will rotate whilst moving in a longitudinal direction.



The invention is based on forcibly guiding movement of the rod in the container in a manner which makes it impossible to rotate or twist the rod in relation to the container and therewith effect unpermitted engagement and disengagement of the coupling means 6, irrespective of whether the rod is moving or stationary.

The guide means herefor may conveniently be mounted within the open part of the container distal from the needle 3.

It will be understood that the invention is not restricted to the aforescribed and illustrated exemplifying embodiments thereof and that modifications can be made within the scope of the invention defined in the following Claims.

CLAIMS

1. A syringe (1) which comprises a rod (5) which can be moved reciprocatingly in relation to a container (2) and one end of which has the form of a needle (3) or is able to coact with a needle, and which further comprises a piston (4) which coacts with the rod, and coupling means (6) for connecting and disconnecting the piston to and from the rod, wherein said coupling means assumes a connecting state when the piston is drawn by the rod from a position proximate to the needle to a position in which it is distanced from the needle, and is brought to a disconnecting or disconnected state when the piston is pressed by the rod towards the needle, and wherein said coupling means comprises support and/or slide surfaces (5k', 5k) on that part of the rod which is proximal to the needle and opposing and coacting support and/or slide surfaces (4k', 4k) on the piston, characterized in that the first support and/or slide surfaces (4k') located on the piston nearest the needle (3) are inclined (c) to an extent such as to cause the piston (4) to rotate about a container centre line, among other centre lines, as the rod (5) moves towards the needle (3).

2. A syringe according to Claim 1, characterized in that the angle of inclination (c) is such that as the rod moves towards the needle and after moving through a short path, such as less than one-half the maximum movement path of the rod in the container, the piston will rotate so as to disengage the first support and/or slide surfaces (4k) on the piston from the corresponding first support and/or slide surfaces (5k') and therewith bring the coupling means (6) to a disconnected state.

3. A syringe according to Claim 2, characterized in that said short movement path is less than one-quarter of the maximum movement path of said rod.








4. A syringe according to Claim 1, 2 or 3, characterized in that the first support and/or slide surfaces (5k') on the rod (5) are configured for parallel, linear or punctiform coaction with the corresponding first support and/or slide surfaces (4k') on the piston.

5. A syringe according to Claim 1, characterized in that the first support and/or slide surfaces (4k', 5k') on the piston and/or on the rod define an angle of between 85° and 20° with a centre line on the piston or the rod, among others.

6. A syringe according to Claim 1, characterized in that the rod is straight and is mounted so as to move reciprocatingly in the container without twisting.

7. A syringe according to Claim 1, characterized in that the second support and/or slide surfaces (4k) on the piston and located distal from the needle are so inclined (c') that as the rod is moved away from the needle (3) the second support and/or slide surfaces on the rod, these surfaces holding the corresponding second support and/or slide surfaces (4k) on the piston in mutually coacting or mutually engaged position, subject the piston to a force which rotates the piston about a container centre line, among others.

8. A syringe according to Claim 7, characterized in that the second support and/or slide surfaces on the rod are configured for parallel, linear or punctiform coaction with corresponding second support and/or slide surfaces on the piston.



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 93/00698

<b>A. CLASSIFICATION OF SUBJECT MATTER</b>		
IPC5: A61M 5/315, A61M 5/50 According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b>		
Minimum documentation searched (classification system followed by classification symbols)		
IPC5: A61M		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X,P	SE, A, 9101204 (NILS GÖRAN HELLDIN ET AL), 23 October 1992 (23.10.92), page 7, line 18  -- -----	1-5,7-8
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
<p>* Special categories of cited documents</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"Z" document member of the same patent family</p>		
Date of the actual completion of the international search		Date of mailing of the international search report
19 November 1993		01 -12- 1993
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer  May Hallne Telephone No. +46 8 782 25 00

01/10/93

PCT/SE 93/00698

Form PCT/ISA/210 (patent family annex) (July 1992)